

## CONCEALED ZD-5000 MODEL



### Application Purpose

- For drywall construction
- For installation in part- or room-height prewall installations
- For installation in room-height installation walls
- Suitable for wall-hung WCs with projection up to 70cm
- For single flush, dual flush or stop-and-go flush

### Characteristics

- Self-supporting frame, powder-coated
- Frame with  $\varnothing$  9 mm drilling holes for fastening in wood frame construction
- Leg support , infinity variable in height
- Non-slip leg supports
- Connection bend can be installed without tools at different depths
- Fastening for connection bend, sound-absorbing
- Concealed cistern with front actuation, fully insulated against condensation
- Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection at the top

## CONCEALED ZD-5000 MODEL

- Protection box for service opening can be cut to length, suitable for surface-even actuator plates

### Technical data

- |  |                   |
|--|-------------------|
| • Flow Pressure                        | 0.1-10 bar        |
| • Flush volume , factory setting       | 6 and 3           |
| • Flush volume large, adjustment range | 4.5 / 6 / 7.5 Ltr |
| • Flush Volume small, adjustment range | 3-4 / 5 Ltr       |

### Scope of delivery

- Protection box for service opening
- Connection bend 90°
- 2 Protection plugs
- Adapter socket
- 2 threaded rods
- Fastening material